


Termocoppia con guaine e canotto in ceramica + inserto ad isolamento minerale (MgO)

Thermocouple with ceramic protection tube and rod + mineral insulated (MgO) insert



Tolleranza termoelemento secondo la norma CEI EN 60584-1 Classe 1
Tolerances thermoelement according to CEI EN 60584-1 Class 1
Tolleranze dimensionali +/- 3% - Dimensional tolerances +/- 3%



Lunghezza L_s
Length

02	100 mm
03	150 mm
04	200 mm
05	250 mm
06	300 mm
07	350 mm
08	400 mm
09	450 mm
10	500 mm
11	550 mm
12	600 mm
13	650 mm
14	700 mm
15	750 mm
16	800 mm
17	850 mm
18	900 mm
19	950 mm
20	1000 mm
21	1050 mm
22	1100 mm
23	1150 mm
24	1200 mm
25	1250 mm
26	1300 mm
27	1350 mm
28	1400 mm
29	1450 mm
30	1500 mm
31	1550 mm
32	1600 mm
33	1650 mm
34	1700 mm
35	1750 mm
36	1800 mm
37	1850 mm
38	1900 mm
39	1950 mm
40	2000 mm





Tutte le quote sono espresse in mm
All dimensions are in millimeters

SETER s.r.l. Data: 16-10-2014 Revisione n°: 01 del 02-01-2017 Disegnato: 001 Approvato: 004

Massime temperature di lavoro consigliate $^\circ\text{C}$
Advised maximum operating temperatures $^\circ\text{C}$

Tipo termocoppia Thermocouple type	Uso continuo Continuous use	Uso intermittente Intermittent use
K (NiCr-Ni)	950 $^\circ\text{C}$	1150 $^\circ\text{C}$
N (Nicrosil-Nisil)	1020 $^\circ\text{C}$	1150 $^\circ\text{C}$



Tipo termocoppia
Thermocouple type

K	N
(NiCr-Ni)	(Nicrosil-Nisil)
2	3

Guaine di protezione
Protection tube

Guaina esterna Outer protection tube (D2)	C 610 (AL203 60%) (EN.60.672-DIN VDE 0335)	C 610 (AL203 60%) (EN.60.672-DIN VDE 0335)
Guaina interna Inner protection tube (D3)	—	C 610 (AL203 60%) (EN.60.672-DIN VDE 0335)
	15	16

SETER®

SETER s.r.l. Fiorano Modenese Modena Italy
commerciale@seter.it www.seter.it
tel. 0536-843454 fax 0536-927199

T 1 2 . 0 1 . 0 0